


Rūcā

Interior High Sheen Emulsion

An Exquisite Water-based Acrylic Emulsion Paint for Distinctive Interiors

PRODUCT FEATURES

DRYING TIME



TOUCH DRY
30 MINUTES

AVAILABLE PACKS

1L, 4L, 10L

SHADE REFERENCE

RUCA Shadecard / Nebula

FINISH



HIGH SHEEN

COVERAGE

140-150 sq.ft/2 coats / litre

*Coverage varies depend on the method of application and absorption of the substrate and its condition

COLOURS AVAILABLE

1261

SHADES AVAILABLE

HOW TO APPLY

SURFACE PREPRATION

- Ensure that the surface is clean and free from dampness, dirt and other contamination.
- For areas severally affected by algae and fungi, ensure that the surface is completely cleaned before initiating the painting process.
- Sand the surface using Emery Paper No.180 and clean thoroughly. Ensure that no loose particles are sticking to the wall.
- Freshly plastered surfaces must be allowed to cure completely. The coating process can be started after a minimum period of 30 days.

APPLICATION PROCEDURE

- Apply 2 coats of Aquafresh wall primer / Altura Primer with an interval of 4 - 5 hrs between subsequent coats.
- Undulations in the wall can be leveled using MRF Vilasa wall putty.
- The putty should be used between the first and second coat of Aquafresh / Altura Primer and sanding of the putty should be done as per recommendation.
- Apply 2 coats of Ruca White/shades with an interval of 3 to 4 hours between subsequent coats after subjecting the second coat of Aquafresh / Altura Primer to sanding using Emery No.320
- Sanding of the first coat of Ruca White / Shade can be done with Emery No.600.
- The number of coats of topcoat depends on the chosen colour. Darker shades may require additional coats

ADDITIONAL INFORMATION

PRODUCT DISCLAIMER

- The information furnished above are true to the best of our knowledge. The properties specified were tested under controlled conditions. The results may vary depending on the test conditions, condition of the substrate and the test method employed. We are not liable for factors that are beyond our knowledge and control

PRECAUTIONS

- The substrate to be coated should be free from dampness as it directly relates to premature paint failure
- The product should be applied at temperatures falling between 20°C to 40°C for optimum performance. Humidity above 75 % is also not favorable
- The product should be stored in a dry, cool and well ventilated place and avoid direct sunlight
- Apply the thinned paint within 24 hours. For tinting, use MRF Vapocure Paints machine colourants only

MRF
Vapocure
Paints



PRODUCT BENEFITS

Advantages

- Low Odor
- Smooth and Silky finish
- Tough and durable
- Antibacterial and Antiviral
- Excellent scrub and stain resistance
- Best in class washability

Where to use

Designed for use on cement plastered interior walls

TECHNICAL INFO

Thinner Intake	- 30 – 40 %
Specific gravity	- 1.32 ± 0.03
Non Volatile Matter	- 57.00 ± 2
Typical thickness	- 40 – 45microns/coat
Sheen @ 60°	- 22-28 units
VOC	- < 50 g /l
Recommended Thinner	- Potable Water
Method of application	- Brush / Roller

RESTRICTION OF HAZARDOUS SUBSTANCES

Lead is not involved at any stage of the manufacturing of the product. Lead content in the film does not exceed 90 parts per million

SAFETY FEATURES

- Use proper PPEs (Personal Protective Equipments) while handling the paint material.
- For more details on safety, refer the MSDS of the product

SHELF LIFE

3 years from the month of manufacturing for an unopened original container.